## NSN 4720-00-922-1376

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-922-1376

| Thread Class:   |
|---|
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.000 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 1.282 inches  |
| Minimum Inside Bending Radius:  |
| 5.000 inches  |
| Connection Style:   |
| Swivel nut, flareless 2nd end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Features Provided:  |
| Electrostatic discharge capability                                    |
| Thready Qty Per Inch (tpi):   |
| 12 2nd end  |
| Burst Test Pressure:  |
| 3600.0 pounds per square inch   |
| Layer Composition And Location:                                       |
| Outer layer braided corrosion resistant steel wire                    |
| Maximum Operating Pressure:   |
| 1000.0 pounds per square inch   |
| Thread Size:  |
| 1.312 inches 2nd end  |
| Seat Angle:   |
| 12.0 degrees 2nd end  |
| Hydrostatic Test Pressure:  |
| 1800.0 pounds per square inch   |
| Flow Angle:   |
| 45.0 degrees 2nd end  |
| Outer Covering Environmental Protection:                              |
| Corrosion resistant   |

Convoluted

**Inside Surface Condition:** 

## NSN 4720-00-922-1376

Nonmetallic Hose Assembly - Page 2 of 2



| <b>Measuring Method And Length:</b> |
|-------------------------------------|
| 18.500 inches working               |
| Media For Which Designed:           |
| Fluid single response               |
| Thread Series Designator:           |
| Un 2nd end                          |
| Shelf Life:                         |
| N/a                                 |
| Unit Of Measure:                    |
|                                     |
| Demilitarization:                   |
| No                                  |

**Fiig:** A542a0