Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-922-2078

| Cross Sectio | onal Shape: |
|--------------------------|---|
| Round | |
| Thread Class | S: |
| 2b 1st end | |
| Thread Direc | ction: |
| Right-hand 1 | st end |
| Inside Diame | eter: |
| 0.250 inches | |
| Tempurature | e Rating: |
| -40.0 degrees | s fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diar | neter: |
| 0.438 inches | |
| Minimum Ins | side Bending Radius: |
| 2.500 inches | |
| Exterior Cold | or: |
| Natural | |
| Connection | Style: |
| Swivel nut fla | ire 1st end |
| End Connec | tion Design: |
| Straight 2nd e | end |
| Connection [·] | Туре: |
| Threaded inte | ernal tube 1st end |
| Burst Test P | ressure: |
| 1600.0 pound | ds per square inch |
| Layer Comp | osition And Location: |
| 1st layer rubb | per impregnated braided fabric and outer layer molded rubber, synthetic |
| Maximum O | perating Pressure: |
| 400.0 pounds | s per square inch |
| Thread Size: | |
| 0.438 inches | 1st end |
| Seat Angle: | |
| 45.0 degrees | 1st end |
| Hydrostatic [·] | Test Pressure: |
| 800.0 pounds | s per square inch |
| Outer Cover | ing Environmental Protection: |
| Abrasion resi | stant and oil resistant and ozone resistant and grease resistant |
| Vacuum In T | orr: |
| 254.0 | |
| Inside Surfa | ce Condition: |
| Smooth | |
| Measuring N | lethod And Length: |
| 19.000 inches | 6 |



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0