NSN 4720-00-923-0399

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-923-0399

Inside Diameter:				
0.212 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response				
Outside Diameter:				
Between 0.360 inches and 0.390 inches				
Minimum Inside Bending Radius:				
1.500 inches				
Connection Style:				
Swivel nut, flareless 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
12.0 degrees 2nd end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Outer Covering Environmental Protection: Corrosion resistant				
-				
Corrosion resistant				
Corrosion resistant Inside Surface Condition:				
Corrosion resistant Inside Surface Condition: Smooth				
Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length:				

NSN 4720-00-923-0399

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

81343-as117 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0