

View Online at <https://aerobasegroup.com/nsn/4720-00-923-1061>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Outside Diameter:

0.516 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 2nd end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

18 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.250 inches 2nd end

Seat Angle:

30.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0