

View Online at <https://aerobasegroup.com/nsn/4720-00-923-1936>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.344 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Connection Style:**

Swivel nut with loose or integral clinch sleeve 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

14000.0 pounds per square inch

**Layer Composition And Location:**

1st layer polytetrafluoroethylene impregnated glass fiber and 2nd layer spirally laid corrosion resistant steel wire and 3rd layer spirally laid corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

6000.0 pounds per square inch

**Thread Size:**

0.562 inches 2nd end

**Seat Angle:**

33.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

10.125 inches working

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0