NSN 4720-00-923-1988

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-923-1988

One and Continued Observer
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.437 inches
Minimum Inside Bending Radius:
5.750 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
88.250 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-00-923-1988

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0