Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-923-2234

Cr	ross Sectional Shape:
Ro	bund
Th	nread Class:
3b	1st end
Th	nread Direction:
Ri	ght-hand 1st end
Ins	side Diameter:
0.1	188 inches
Те	empurature Rating:
-65	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Οι	utside Diameter:
0.3	312 inches
Mi	nimum Inside Bending Radius:
2.0	000 inches
Ex	tterior Color:
Na	atural
Co	onnection Style:
Sv	vivel nut, flareless 1st end
En	nd Connection Design:
Sti	raight 1st end
Co	onnection Type:
Th	readed internal tube 1st end
Th	nready Qty Per Inch (tpi):
20	1st end
Βι	urst Test Pressure:
12	2000.0 pounds per square inch
La	yer Composition And Location:
Οι	uter layer braided corrosion resistant steel wire
Ма	aximum Operating Pressure:
15	00.0 pounds per square inch
Th	nread Size:
0.4	438 inches 1st end
Se	eat Angle:
12	.0 degrees 1st end
Ну	/drostatic Test Pressure:
30	00.0 pounds per square inch
Va	acuum In Torr:
50	.8
Ins	side Surface Condition:
Sn	nooth
Me	easuring Method And Length:

21.500 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Air single response and alcohol, ethyl single response and fuel/oil, hydrocarbon single response and water, fresh single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0