NSN 4720-00-923-4077

Cross Sectional Shape:

Between 0.844 inches and 0.906 inches

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-923-4077

Tempurature Rating:
-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 1.125 inches and 1.187 inches
Minimum Inside Bending Radius:
5.500 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
203.2
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.875 inches working and 18.125 inches working

NSN 4720-00-923-4077

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0