N/a

Nonmetallic Hose Assembly - Page 1 of 2



layer braided corrosion

View Online at https://aerobasegroup.com/nsn/4720-00-924-8247

/iew Online at https://aerobasegroup.com/nsn/4720-00-924-8247	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.219 inches	
Fempurature Rating:	
67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response	
Dutside Diameter:	
0.250 inches	
Minimum Inside Bending Radius:	
3.000 inches	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
16000.0 pounds per square inch	
_ayer Composition And Location:	
Ist layer spirally laid corrosion resistant steel wire and 2nd layer spirally laid corrosion resistant steel wire and out	er l
esistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	
5000.0 pounds per square inch	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
30.750 inches	
Fhread Series Designator:	
Jnf 1st end	
Specification Data:	
- 31343-as621 professional/industrial association standard	
Shelf Life:	
Shelf Life:	

NSN 4720-00-924-8247

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0