

View Online at <https://aerobasegroup.com/nsn/4720-00-925-1307>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.900 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response

**Outside Diameter:**

1.100 inches

**Minimum Inside Bending Radius:**

7.400 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

1.312 inches 1st end

**Seat Angle:**

33.0 degrees 1st end

**Hydrostatic Test Pressure:**

400.0 pounds per square inch

**Outer Covering Environmental Protection:**

Incombustible

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

42.100 inches working and 42.400 inches working

**Special Features:**

Equipped with fire sleeve

**Thread Series Designator:**

Un 1st end

**Specification Data:**

98897-3+91459-103 manufacturers source control

**Fsc Application Data:**

Fuselage section, airframe

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A542a0