Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-928-4451

| Cross Sectional Shaney |
|---|
| Cross Sectional Shape: Round |
| |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| Between 0.234 inches and 0.266 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.453 inches and 0.500 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Connection Style: |
| Gasket seal / optional end 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal boss 1st end |
| Burst Test Pressure: |
| 1250.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fabric and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Hydrostatic Test Pressure: |
| 400.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant and weatherproof and oil resistant and water resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 12.000 inches excluding end fittings |
| Media For Which Designed: |
| Air single response |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| |

NSN 4720-00-928-4451

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0