## NSN 4720-00-928-4853

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-928-4853

Thread Class:			
3b 2nd end			
Thread Direction:			
Right-hand 2nd end			
Inside Diameter:			
0.312 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
0.438 inches			
Angle Between Rigid Elbow Fittings In Deg:			
135.0			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Elbow 1st end			
Connection Type:			
Threaded internal tube 2nd end			
Features Provided:			
Electrostatic discharge capability			
Thready Qty Per Inch (tpi):			
18 1st end			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1500.0 pounds per square inch			
Thread Size:			
0.562 inches 2nd end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Inside Surface Condition:			

Unf 2nd end

**Thread Series Designator:** 

Smooth

## NSN 4720-00-928-4853

Nonmetallic Hose Assembly - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0