NSN 4720-00-930-0418

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-930-0418

2b 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
120.0 degrees fahrenheit single response
Outside Diameter:
1.187 inches
Minimum Inside Bending Radius:
16.000 inches
Angle Between Rigid Elbow Fittings In Deg:
90.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 2nd end
Features Provided:
Internal support
Thready Qty Per Inch (tpi):
14 2nd end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
625.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1250.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Ozone resistant

NSN 4720-00-930-0418

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
23.437 inches and 23.687 inches	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A542a0