## NSN 4720-00-930-2317



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-930-2317 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees celsius single response **Minimum Inside Bending Radius:** 6.005 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 750.0 pounds per square inch **Thread Size:** 1.062 inches 1st end **Hydrostatic Test Pressure:** 1500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 26.750 inches working and 27.250 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4720-00-930-2317

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0