## NSN 4720-00-930-9810

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-930-9810 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.578 inches **Minimum Inside Bending Radius:** 3.380 inches **Connection Style:** Swivel nut, gasket seal 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer braided wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 5000.0 pounds per square inch

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

8.188 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

## NSN 4720-00-930-9810

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0