## NSN 4720-00-931-8305

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-931-8305

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response   |
| Exterior Color:   |
| Natural   |
| Angle Between Rigid Elbow Fittings In Deg:  |
| 45.0  |
| Connection Style:   |
| Swivel nut flare 2nd end  |
| End Connection Design:  |
| Elbow 2nd end   |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Features Provided:  |
| Nuts drilled for lockwire   |
| Burst Test Pressure:  |
| 1000.0 pounds per square inch   |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire  |
| Maximum Operating Pressure:   |
| 200.0 pounds per square inch  |
| Thread Size:  |
| 0.750 inches 2nd end  |
| Seat Angle:   |
| 37.0 degrees 2nd end  |
| Flow Angle:   |
| 45.0 degrees 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 13.130 inches working and 13.370 inches working   |
| Test Data Document:   |
| 81349-mil-e-8595 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |
| Thread Series Designator:   |
| Unf 2nd end   |
| Shelf Life:   |

## NSN 4720-00-931-8305

Nonmetallic Hose Assembly - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV  | еа  | SU  | ıre: |

--

Demilitarization:

No

Fiig:

A542a0