

View Online at <https://aerobasegroup.com/nsn/4720-00-932-7765>

Cross Sectional Shape:

Round

Inside Diameter:

0.500 inches

Outside Diameter:

0.688 inches

Minimum Inside Bending Radius:

5.000 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Exterior Color:

Natural

End Connection Design:

Straight 2nd end

Connection Type:

Unthreaded external tube 2nd end

Burst Test Pressure:

2800.0 pounds per square inch

Layer Composition And Location:

Outer layer braided bronze wire

Maximum Operating Pressure:

150.0 pounds per square inch

Hydrostatic Test Pressure:

300.0 pounds per square inch

Vacuum In Torr:

25.4

Measuring Method And Length:

15.800 inches

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Special Features:

First end id 0.379 in. Porm 0.001 in. To a depth of 0.313 in., second end od 0.375 in. And 0.562 in. From end

Test Data Document:

80064-845-1889636 rev-b assembly aa drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0