

View Online at <https://aerobasegroup.com/nsn/4720-00-932-7765>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.500 inches

**Outside Diameter:**

0.688 inches

**Minimum Inside Bending Radius:**

5.000 inches

**Inner Conveying Tube Style:**

Annular close-pitch corrugated

**Exterior Color:**

Natural

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Unthreaded external tube 2nd end

**Burst Test Pressure:**

2800.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided bronze wire

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Vacuum In Torr:**

25.4

**Measuring Method And Length:**

15.800 inches

**Outside Diameter Tube Accommodated:**

0.625 inches 1st end

**Special Features:**

First end id 0.379 in. Porm 0.001 in. To a depth of 0.313 in., second end od 0.375 in. And 0.562 in. From end

**Test Data Document:**

80064-845-1889636 rev-b assembly aa drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0