Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-933-3759

01035 3	ectional Shape:
Round	
Thread (Class:
2b 1st er	nd
Thread I	Direction:
Right-ha	nd 1st end
Inside D	liameter:
0.625 inc	ches
Tempura	ature Rating:
-40.0 deo	grees fahrenheit and 200.0 degrees fahrenheit single response
Outside	Diameter:
1.090 inc	ches
Minimur	m Inside Bending Radius:
8.000 inc	ches
Exterior	Color:
Black	
Connect	tion Style:
Swivel n	ut flare 1st end
End Cor	nnection Design:
Straight 2	2nd end
Connect	tion Type:
Threaded	d internal tube 1st end
Thready	v Qty Per Inch (tpi):
12 1st er	nd
Burst Te	est Pressure:
11000.0	pounds per square inch
Layer Co	omposition And Location:
1st layer	spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber, chloroprene
Maximu	m Operating Pressure:
2750.0 p	bounds per square inch
Thread S	Size:
1.063 inc	ches 1st end
Seat Ang	gle:
37.0 deg	prees 1st end
Hydrost	atic Test Pressure:
5500.0 p	bounds per square inch
Flow An	igle:
90.0 deg	prees 1st end
Inside S	Surface Condition:
Smooth	
Measuri	ng Method And Length:
78.500 ir	nches

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon and water, fresh and water, salt single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0