NSN 4720-00-933-3770



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-933-3770 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.125 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 100.0 degrees fahrenheit single response **Outside Diameter:** 0.500 inches **Exterior Color:** Black **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided rayon cord and 1st layer braided polyester cord or 1st layer braided cotton cord or 2nd layer braided cotton cord or outer layer molded rubber, synthetic **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 37.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 16.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:**

Unit Of Measure:

N/a

Unf 2nd end Shelf Life:

NSN 4720-00-933-3770

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0