

View Online at <https://aerobasegroup.com/nsn/4720-00-936-2146>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.750 inches

Minimum Inside Bending Radius:

11.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

1.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.000 inches working

Special Features:

Pressure port boss per and 10050-4, 7/16-20 thd in first end fitting

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0