NSN 4720-00-936-2147

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.438 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-936-2147

-65.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response		
Outside Diameter:		
0.859 inches		
Minimum Inside Bending Radius:		
5.750 inches		
Connection Style:		
Swivel nut flare 2nd end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Burst Test Pressure:		
14000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer molded rubber, chloroprene		
Maximum Operating Pressure:		
3000.0 pounds per square inch		
Thread Size:		
0.750 inches 2nd end		
Seat Angle:		
37.0 degrees 2nd end		
Hydrostatic Test Pressure:		
7000.0 pounds per square inch		
Flow Angle:		
45.0 degrees 2nd end		
Outer Covering Environmental Protection:		
Fuel resistant and oil resistant and mildew resistant and cold resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
37.500 inches working		
Media For Which Designed:		
Fuel/oil, hydrocarbon single response		

NSN 4720-00-936-2147

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	--------------------

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0