NSN 4720-00-936-3548

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.200 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-936-3548

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

c	Outside Diameter:
	0.300 inches
	Exterior Color:
	Natural
	Connection Style:
	Swivel nut flare 1st end
	End Connection Design:
	Straight 1st end
	Connection Type:
	Threaded internal tube 1st end
T	Thready Qty Per Inch (tpi):
2	20 1st end
Е	Burst Test Pressure:
1	2000.0 pounds per square inch
L	ayer Composition And Location:
C	Outer layer braided corrosion resistant steel wire
Ν	Maximum Operating Pressure:
1	500.0 pounds per square inch
T	hread Size:
0	0.438 inches 1st end
S	Seat Angle:
3	37.0 degrees 1st end
H	lydrostatic Test Pressure:
5	000.0 pounds per square inch
C	Outer Covering Environmental Protection:
C	Corrosion resistant and hydraulic solution resistant and oil resistant
٧	/acuum In Torr:
5	50.8
li	nside Surface Condition:
S	Smooth
Λ	Measuring Method And Length:
9	4.100 inches working and 96.100 inches working

NSN 4720-00-936-3548

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed
-------	-----	-------	--------	----

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Fsc Application Data:

Pylons, aircraft

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0