## NSN 4720-00-936-3613

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-936-3613

Cross Sectional Shape:			
Round			
Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.250 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
0.688 inches			
Minimum Inside Bending Radius:			
4.000 inches			
Exterior Color:			
Black			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 2nd end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability and reusable end fittings			
Burst Test Pressure:			
20000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
5000.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
37.0 degrees and 45.0 degrees 1st end			
Hydrostatic Test Pressure:			
10000.0 pounds per square inch			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
12.750 inches			
Media For Which Designed:			

## NSN 4720-00-936-3613

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:
	0000	_00.9.	

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0