NSN 4720-00-936-4886

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-936-4886

Tempurature Rating:			
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response			
Outside Diameter:			
Between 0.455 inches and 0.490 inches			
Minimum Inside Bending Radius:			
2.500 inches			
Connection Style:			
Swivel nut, flareless 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability			
Burst Test Pressure:			
14000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
0.562 inches 1st end			
Seat Angle:			
12.0 degrees 1st end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Corrosion resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
11.000 inches working			
Thread Series Designator:			
Unjf 1st end			

NSN 4720-00-936-4886

Nonmetallic Hose Assembly - Page 2 of 2



Spe	cific	ation	Data:
-----	-------	-------	-------

81343-as115 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0