

View Online at <https://aerobasegroup.com/nsn/4720-00-937-2822>

Cross Sectional Shape:

Round

Inside Diameter:

2.000 inches

Outside Diameter:

2.656 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Mil mil-h-370, type 2, size 6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Quick Disconnect Size:

2.000 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

Fitting Component And Surface Treatment:

Complete fitting anodize 1st end

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Not identical

Burst Test Pressure:

400.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

First End Fitting/component And Material:

Complete fitting-aluminum alloy 356 temper 6 or aluminum alloy, qq-a-601, temper 5

Hydrostatic Test Pressure:

125.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.0 feet excluding end fittings

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81349-mil-prf-370 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-370 spec.