Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-938-8709

Cross Sectional Shape		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Minimum Inside Bendi	na Radius:	
0.750 inches	iy nadius.	
Angle Between Rigid E	Ibow Fittings In Dog.	
90.0	isow i ittiliyə ili Dey.	
Solution Style:		
Swivel nut, flareless 1st	end	
End Connection Desig		
Elbow 1st end		
Connection Type:		
Threaded internal tube 1	stand	
Features Provided:	SUCHU	
	apahility	
Electrostatic discharge of <b>Burst Test Pressure</b> :	apability	
	inch	
800.0 pounds per square		
Layer Composition An		
Outer layer braided corre		
Maximum Operating P		
200.0 pounds per square	; INCH	
Thread Size:		
0.562 inches 1st end		
Seat Angle:		
12.0 degrees 1st end		
Hydrostatic Test Press		
400.0 pounds per square	) INCh	
Flow Angle:		
90.0 degrees 1st end		
Outer Covering Enviro	mental Protection:	
Corrosion resistant		
Inside Surface Condition	»n:	
Smooth		
Measuring Method And	Length:	
8.500 inches working		
Media For Which Desig	ned:	
Fluid single response		
Thread Series Designa	tor:	
Unjf 1st end		

## NSN 4720-00-938-8709

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

