

View Online at <https://aerobasegroup.com/nsn/4720-00-939-7598>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.380 inches

Temperature Rating:

-40.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Bolt Circle Diameter:

1.000 inches 2nd end

Flange Thickness:

0.365 inches 2nd end

Outside Diameter:

1.703 inches

Minimum Inside Bending Radius:

9.000 inches

Angle Between Rigid Elbow Fittings In Deg:

150.0

Bolt Hole Quantity:

3 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.688 inches 2nd end

Raised Face Height:

0.250 inches 2nd end

Raised Face Diameter:

1.625 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

1.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

800.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

37.500 inches working

Flange Style:

Triangular 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 00624, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0