NSN 4720-00-939-7647

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-939-7647 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.234 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3200.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer rubber impregnated fabric and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 800.0 pounds per square inch **Thread Size:** 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 1600.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 40.000 inches excluding end fittings **Thread Series Designator:**

N/a

Un 1st end Shelf Life:

NSN 4720-00-939-7647

Nonmetallic Hose Assembly - Page 2 of 2



ı	1	:4	2	B.A.		٠.	ıre:
ι	JH	ш	OI.	IVI	еа	SL	ne:

--

Demilitarization:

No

Fiig:

A542a0