## NSN 4720-00-940-0964

Nonmetallic Hose Assembly - Page 1 of 2



<u> </u>
View Online at https://aerobasegroup.com/nsn/4720-00-940-0964
Cross Sectional Shape:
Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 2nd end
Inside Diameter:
0.188 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 2nd end
Thready Qty Per Inch (tpi):
20 2nd end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

inside Surface Conditio

**Measuring Method And Length:** 

27.500 inches working

**Thread Series Designator:** 

Unf 2nd end

Smooth

## NSN 4720-00-940-0964

Nonmetallic Hose Assembly - Page 2 of 2



Sı	pecif	icati	on Da	ta:
----	-------	-------	-------	-----

07482-r463c0276al manufacturers source control

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0