## NSN 4720-00-940-0965

**Cross Sectional Shape:** 

Nuts drilled forlockwire

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-940-0965

Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.188 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response		
Outside Diameter:		
0.312 inches		
Minimum Inside Bending Radius:		
2.000 inches		
Connection Style:		
Swivel nut flare 2nd end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Electrostatic discharge capability		
Burst Test Pressure:		
12000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer braided corrosion resistant steel wire		
Maximum Operating Pressure:		
1500.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
37.0 degrees 2nd end		
Hydrostatic Test Pressure:		
3000.0 pounds per square inch		
Flow Angle:		
90.0 degrees 2nd end		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
8.500 inches working		
Special Features:		

## NSN 4720-00-940-0965

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	<b>Designator:</b>
--------	--------	--------------------

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0