Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-940-3485

| View Online at https://aerobasegroup.com/nsn/4720-00-940-3485 |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.750 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.031 inches |
| Minimum Inside Bending Radius: |
| 7.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Layer Composition And Location: |
| 1st layer braided cotton cord and outer layer molded rubber |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Abrasion resistant and mildew resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 34.000 inches excluding end fittings and 35.000 inches excluding end fittings |
| Thread Series Designator: |
| Unf 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 4720-00-940-3485

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

