

View Online at <https://aerobasegroup.com/nsn/4720-00-940-8396>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.219 inches

**Outside Diameter:**

0.625 inches

**Minimum Inside Bending Radius:**

3.250 inches

**Exterior Color:**

Natural

**Hose Or Tubing Specification/std Data:**

Mil-h-38390, size 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Nipple steel comp 321 all ends

**Fitting Component And Surface Treatment:**

Nipple passivate 1st end

**Connection Type:**

Threaded external pipe 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

16000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded plastic err-100

**Maximum Operating Pressure:**

4000.0 pounds per square inch

**Thread Size:**

0.250 inches 1st end

**Hydrostatic Test Pressure:**

8000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

20.000 inches

**Special Features:**

Inner conveying tube material-plastic, tetrafluoroethylene

**Thread Series Designator:**

Npt 1st end

**Specification Data:**

Mil-h-38390, size 4 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-38390 spec.