NSN 4720-00-941-5284

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-941-5284

Cross Sectional Shape:	
Round	

Thread Class: 3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.678 inches and 0.719 inches

Tempurature Rating:

-65.0 degrees fahrenheit single response

Outside Diameter:

1.219 inches

Minimum Inside Bending Radius:

7.750 inches

Hose Or Tubing Specification/std Data:

Mil-h-8788, size 12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil ms28761-12 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut with loose or integral clinch sleeve 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Socket aluminum alloy 2nd end

Fitting Component And Surface Treatment:

Nut cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.062 inches 1st end

NSN 4720-00-941-5284

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and mildew resistant and cold resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
78.500 inches working
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Specification Data:
96906-ms28762 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-h-8788 spec.