NSN 4720-00-942-8147

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-942-8147

View Offiline at https://defobasegroup.com/nish/4/20-00-342-014/
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.789 inches
Minimum Inside Bending Radius:
6.500 inches
Hose Or Tubing Specification/std Data:
Mil mil-h-27267 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Socket steel 2nd end
Fitting Component And Surface Treatment:
Socket cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 2nd end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
5000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:

1.062 inches 2nd end

Thread Size:

1000.0 pounds per square inch

NSN 4720-00-942-8147Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.500 inches working
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-plastic, polytetrafluoroethylene
Supplementary Features:
This item has been reviewed for asbestos material. The current approved source, 78286, has indicated their part number contained
asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984
Thread Series Designator:
Unj 2nd end
Specification Data:
96906-ms8005 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A542a0