Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-942-8149

Creas Sastianal Shana
Cross Sectional Shape: Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.188 inches and 0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response
Outside Diameter:
Between 0.406 inches and 0.453 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Silver
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure: 6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Inside Surface Condition:
Smooth
Measuring Method And Length: 29.375 inches and 30.375 inches

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0