

View Online at <https://aerobasegroup.com/nsn/4720-00-942-8315>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.852 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

1.000 inches

**Minimum Inside Bending Radius:**

9.625 inches

**Angle Between Rigid Elbow Fittings In Deg:**

325.0

**Hose Or Tubing Specification/std Data:**

Sae as604, size 16-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Swivel nut, flareless 1st end

**End Connection Design:**

Elbow 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting passivate 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

12 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

12000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

1.312 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

21.625 inches working

**Special Features:**

Inner conveying tube material-plastic, tetrafluoroethylene

**Thread Series Designator:**

Unj 1st end

**Specification Data:**

81343-as626 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0