NSN 4720-00-943-1817

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/4720-00-943-1617
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Hose Or Tubing Specification/std Data:
Mil mil-h-27267, size 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Second End Relationship With First End:
Not identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:

37.0 degrees 2nd end

Seat Angle:

0.438 inches 1st end

NSN 4720-00-943-1817Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.000 inches working
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-plastic, polytetrafluoroethylene
Supplementary Features:
This item has been reviewed for asbestos material. The current approved source, 96906, has indicated their part number contained
asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8005 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A542a0