Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-947-2118

Cross	Sectional Shape:
Round	3
Threa	d Class:
3b 1st	end
Threa	d Direction:
Right-	hand 1st end
Inside	Diameter:
0.188	inches
Temp	urature Rating:
-65.0 (degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outsi	de Diameter:
0.312	inches
Minim	um Inside Bending Radius:
2.000	inches
Conne	ection Style:
Swive	I nut flare 1st end
End C	connection Design:
Straig	ht 1st end
Conne	ection Type:
Threa	ded internal tube 1st end
Featu	res Provided:
Electro	ostatic discharge capability
Burst	Test Pressure:
12000	.0 pounds per square inch
Layer	Composition And Location:
Outer	layer braided corrosion resistant steel wire
Maxin	num Operating Pressure:
1500.0) pounds per square inch
Threa	d Size:
0.438	inches 1st end
Seat A	Angle:
37.0 d	egrees 1st end
Hydro	ostatic Test Pressure:
3000.0) pounds per square inch
Vacuu	ım In Torr:
50.8	
Inside	Surface Condition:
Smoot	th
Measu	uring Method And Length:
12.500	Dinches working
Threa	d Series Designator:
Unf 1s	st end

NSN 4720-00-947-2118

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

