NSN 4720-00-948-3150

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-948-3150

Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
Between 0.984 inches and 1.040 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response			
Outside Diameter:			
Between 1.359 inches and 1.453 inches			
Minimum Inside Bending Radius:			
8.000 inches			
Exterior Color:			
Natural			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
12 1st end			
Layer Composition And Location:			
1st layer braided steel wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
100.0 pounds per square inch			
Thread Size:			
1.938 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
200.0 pounds per square inch			
Outer Covering Environmental Protection:			
Abrasion resistant and oil resistant and weatherproof			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
34.600 inches working			
Media For Which Designed:			

Fuel/oil, hydrocarbon and air and water, fresh single response

NSN 4720-00-948-3150

Nonmetallic Hose Assembly - Page 2 of 2



Test Data Document:

10001-1550309 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread	Series	Design	nator:
	0000	_00.9.	

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0