NSN 4720-00-949-3289

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-949-3289

Round		
Thread Class:		
2b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
Between 1.968 inches and 2.080 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response		
Outside Diameter:		
Between 2.718 inches and 2.906 inches		
Minimum Inside Bending Radius:		
22.000 inches		
Exterior Color:		
Natural		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Thready Qty Per Inch (tpi):		
12 1st end		
Layer Composition And Location:		
1st layer braided steel wire and outer layer molded rubber, synthetic		
Maximum Operating Pressure:		
100.0 pounds per square inch		
Thread Size:		
2.500 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
200.0 pounds per square inch		
Outer Covering Environmental Protection:		
Abrasion resistant and oil resistant and weatherproof		
Inside Surface Condition:		

19.800 inches working

Smooth

Media For Which Designed:

Measuring Method And Length:

Fuel/oil, hydrocarbon and air and water, fresh single response

NSN 4720-00-949-3289

Nonmetallic Hose Assembly - Page 2 of 2



Test Data Document:

10001-1550309 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Se	ries Des	signator:
-----------	----------	-----------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0