Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-955-9550

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.688 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.938 inches
Minimum Inside Bending Radius:
4.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
3750.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
31.750 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response

## NSN 4720-00-955-9550

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unjf 1st end

Specification Data:

77272-114d4044-2 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0