Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-956-4300

Cross Sectional Shape:         Round         Thread Class:         3b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.125 inches         Tempurature Rating:         oftside Diameter:         0.250 inches         Minimun Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Features Provided:         Icconsection Style:         Straight 1st end         Pare Pressure:         12000.0 pounds per square inch         Hauren Operating Pressure:         12000.0 pounds per square inch         Maximum Operating Pressure:         1300.0 pounds per square inch         Maximum Operating Pressure:         1300.0 pounds per square inch         Straight 1st end         Maximum Operating Pressure:         1300.0 pounds per square inch         Maximum Operating Pressure:         1300.0 pounds per square inch         Maximum Operating Pressure:         1300.0 pounds per squ	
Thread Class:         3b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.125 inches         Tempurature Rating:         0.50 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimun Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Design:         Straight 1st end         Pateede internal tube 1st end         Features Provided:         Electrostatic discharge capability         Burst Tess Pressure:         12000.0 pounds per square inch         Layer Omposition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1350.0 pounds per square inch         Streide:         1500.0 pounds per square inch         Hered Size:         0.37.0 inders 1st end         Seat Angle:      <	Cross Sectional Shape:
Ab Ist and         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.125 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimum Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swiwel nut flare 1st end         End Connection Design:         Straight 1st end         Everor Straight 1st end         Features Provided:         Icconstitic discharge capability         Burst Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         130.0.0 pounds per square inch         Thread Size:         0.375 inches 1st end         Seat Angle:         37.0 indegrees 1st end         Hydrostatic Test Pressure:         1300.0 pounds per square inch         Sure Angle:         37.0 indegrees 1st end         Hydrostatic Test Pressure:	Round
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.125 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimum Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Exterior Style:         Straight 1st end         Paures Provided:         Electrostatic discharge capability         Burst Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         130.0.0 pounds per square inch         Thread Size:         0.375 inches 1st end         Hydrostatic Test Pressure:         3000.0 pounds per square inch         Hydrostatic Test Pressure:         3000.0 pounds per square inch         Hydrostatic Test Pressure:         3000.0 pounds per square inch         Hydrostati	Thread Class:
Right-hand 1st end         Inside Diameter:         0.125 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimun Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Burst Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         150.0, pounds per square inch         Straight:         9.7.0 degrees 1st end         Hydrostatic Test Pressure:         1500.0, pounds per square inch         Maximum Operating Pressure:         1500.0, pounds per square inch         Hydrostatic Test Pressure:         3000.0, pounds per square inch         Hydrostatic Test Pressure:	3b 1st end
Inside Diameter:         0.125 inches         Fempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimun Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Patures Provided:         Electrostatic discharge capability         Bust Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximu Operating Pressure:         150.0.0 pounds per square inch         Steat Angle:         9.7.0 degrees 1st end         Hydrostatic Test Pressure:         1300.0 pounds per square inch         Steat Angle:         9.7.0 degrees 1st end         Hydrostatic Test Pressure:         1300.0 pounds per square inch         Vacuum In Torr:         50.8         Inside Surface Condition:	Thread Direction:
0.125 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimun Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Burst Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1500.0 pounds per square inch         Straight:         0.375 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         3000.0 pounds per square inch         Vacuum In Torr:         50.8         Inside Surface Condition:         Smooth	Right-hand 1st end
Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimum Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Burst Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1500.0 pounds per square inch         Steat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         3000.0 pounds per square inch         Vacuum In Torr:         60.8         Inside Surface Condition:         Sprooth	Inside Diameter:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.250 inches         Minimum Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Burst Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1300.0 pounds per square inch         Stread Size:         0.375 inches 1st end         Set Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         3000.0 pounds per square inch         Hydrostatic Test Pressure:	0.125 inches
Outside Diameter:0.250 inchesMinimum Inside Bending Radius:1.500 inchesExterior Color:Natural or silverConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:1200.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchStraight:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchCurread Size:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchKaumu Operating Pressure:3000.0 pounds per square inchSure Sure State St	Tempurature Rating:
0.250 inchesMinimum Inside Bending Radius:1.500 inchesExterior Color:Natural or silverConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0.0 pounds per square inchSteat Angle:37.0 degrees 1st endHydrostatic Test Pressure:300.0 pounds per square inchCuter layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0.0 pounds per square inchCuter layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0.0 pounds per square inchSuct Angle:37.0 degrees 1st endHydrostatic Test Pressure:300.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Minimum Inside Bending Radius:         1.500 inches         Exterior Color:         Natural or silver         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Burst Test Pressure:         12000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1500.0 pounds per square inch         Thread Size:         0.375 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         3000.0 pounds per square inch         Vacuum In Torr:         50.8         Inside Surface Condition:         Smooth	Outside Diameter:
<ul> <li>1.500 inches</li> <li>Exterior Color:</li> <li>Natural or silver</li> <li>Connection Style:</li> <li>Swivel nut flare 1st end</li> <li>End Connection Design:</li> <li>Straight 1st end</li> <li>Connection Type:</li> <li>Threaded internal tube 1st end</li> <li>Features Provided:</li> <li>Electrostatic discharge capability</li> <li>Burst Test Pressure:</li> <li>12000.0 pounds per square inch</li> <li>Layer Composition And Location:</li> <li>Outer layer braided corrosion resistant steel wire</li> <li>Maximum Operating Pressure:</li> <li>1500.0 pounds per square inch</li> <li>Stread Angle:</li> <li>37.0 degrees 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>3000.0 pounds per square inch</li> <li>Kaumini Torr:</li> <li>50.8</li> <li>Inside Surface Condition:</li> <li>Smooth</li> </ul>	0.250 inches
Exterior Color:Natural or silverConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchFuread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	Minimum Inside Bending Radius:
Natural or silverConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	1.500 inches
Connection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchKucuum In Torr:50.8Inside Surface Condition:Smooth	Exterior Color:
Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchFureur In Torr:50.8Inside Surface Condition:	Natural or silver
End Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchFueration In Torr:50.8Inside Surface Condition:Smooth	Connection Style:
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition:	Swivel nut flare 1st end
Connection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchFureus Ist endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchFureus Ist endSongen Ist endHydrostatic Test Pressure:3000.0 pounds per square inchKacuum In Torr:50.8Inside Surface Condition:Smooth	End Connection Design:
Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	Straight 1st end
Features Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	Connection Type:
Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition:	Threaded internal tube 1st end
Burst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	Features Provided:
<ul> <li>12000.0 pounds per square inch</li> <li>Layer Composition And Location:</li> <li>Outer layer braided corrosion resistant steel wire</li> <li>Maximum Operating Pressure:</li> <li>1500.0 pounds per square inch</li> <li>Thread Size:</li> <li>0.375 inches 1st end</li> <li>Seat Angle:</li> <li>37.0 degrees 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>3000.0 pounds per square inch</li> <li>Vacuum In Torr:</li> <li>50.8</li> <li>Inside Surface Condition:</li> <li>Smooth</li> </ul>	Electrostatic discharge capability
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	Burst Test Pressure:
Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	12000.0 pounds per square inch
Maximum Operating Pressure:1500.0 pounds per square inchThread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	Layer Composition And Location:
1500.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	Outer layer braided corrosion resistant steel wire
Thread Size:0.375 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchVacuum In Torr:50.8Inside Surface Condition:Smooth	Maximum Operating Pressure:
0.375 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	1500.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	0.375 inches 1st end
Hydrostatic Test Pressure: 3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	Seat Angle:
3000.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	37.0 degrees 1st end
Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	Hydrostatic Test Pressure:
50.8 Inside Surface Condition: Smooth	3000.0 pounds per square inch
Inside Surface Condition: Smooth	Vacuum In Torr:
Smooth	50.8
	Inside Surface Condition:
Measuring Method And Length:	Smooth
5	Measuring Method And Length:

19.250 inches and 19.312 inches

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0