

View Online at <https://aerobasegroup.com/nsn/4720-00-956-9500>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.922 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

7000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic err-100

**Maximum Operating Pressure:**

1750.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

107.375 inches working

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0