

Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-00-957-3014
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.188 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch

# Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord

#### Maximum Operating Pressure:

3000.0 pounds per square inch

#### **Thread Size:**

0.375 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### Hydrostatic Test Pressure:

6000.0 pounds per square inch

### Inside Surface Condition:

Smooth

### Measuring Method And Length:

10.000 inches working

#### Media For Which Designed:

Fuel/oil, hydrocarbon single response

## **Thread Series Designator:**

Unf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

**Specification Data:** 

96906-ms28741 government standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

