NSN 4720-00-957-6682



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-957-6682 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.469 inches **Minimum Inside Bending Radius:** 4.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.750 inches working

Thread Series Designator:

Unf 1st end

NSN 4720-00-957-6682

Nonmetallic Hose Assembly - Page 2 of 2



| Sı | pecif | icati | on Da | ta: |
|----|-------|-------|-------|-----|
|----|-------|-------|-------|-----|

81349-mil-h-25579 government specification

Specification Or Standard:

6 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0