## NSN 4720-00-958-5340

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-958-5340

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
1.109 inches
Minimum Inside Bending Radius:
7.380 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Identical ends
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
7.500 inches
Thread Series Designator:
Had Antonia

Unj 1st end

## NSN 4720-00-958-5340

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0