Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-959-0407

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response	
Outside Diameter:	
0.438 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
End Fitting Component And Material:	
Complete fitting aluminum alloy all ends	
Connection Type:	
Threaded internal tube 1st end	
Second End Relationship With First End:	
Identical	
Burst Test Pressure:	
1700.0 pounds per square inch	
First End Swivel Action Capability:	
Not included	
Layer Composition And Location:	
Outer layer molded rubber, synthetic err-100	
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
0.375 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
500.0 pounds per square inch	
Vacuum In Torr:	
254.0	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
40.000 inches working	

NSN 4720-00-959-0407 Nonmetallic Hose Assembly - Page 2 of 2



Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0