NSN 4720-00-959-0455

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-959-0455

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Outside Diameter: |
| 0.688 inches |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 20000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Outer Covering Environmental Protection: |
| Abrasion resistant and water resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 12.000 inches |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A542a0