

View Online at <https://aerobasegroup.com/nsn/4720-00-962-6549>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Temperature Rating:

-25.0 degrees fahrenheit and 150.0 degrees fahrenheit single response

Flange Thickness:

0.560 inches 1st end

Minimum Inside Bending Radius:

9.000 inches

Angle Between Rigid Elbow Fittings In Deg:

180.0

Center To Center Distance Between Bolt Holes Along Width:

1.180 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

2.312 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

3.120 inches 1st end

Flange Width:

2.874 inches 1st end

Connection Style:

Raised swivel w/ gasket groove 1st end

Bolt Hole Diameter:

0.469 inches 1st end

Raised Face Height:

0.020 inches 1st end

Raised Face Diameter:

2.000 inches 1st end

End Flange Construction:

Split 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Raised face flange 1st end

Features Provided:

Self-sealing

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

125.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

190.000 inches working and 194.000 inches working

Flange Style:

Double oval (sae split type flange) 1st end

Special Features:

Long tangent style elbow on one end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0